

Amendments to the Claims:

Please cancel claims 1, 2 and 8 - 10 without prejudice or disclaimer of the subject matter thereof.

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claims 1 and 2 (Canceled)

3. (currently amended) A servo detection control system ~~according to Claim 2, further comprising:~~ comprising:

a head change learning means including:

a means for measuring a servo sector interval, which occurs at the time of head change;

a means for calculating a head-change time difference from a value measured by the servo sector interval measuring means;

and

a means for storing a result of calculation by the calculating means;

a means for compensating a start timing of servo detection after head change using a stored value of the storing means;

wherein the head change learning means further comprises a means for measuring the amount of head skew in a disk radius direction using a writing signal in a servo sector after the head change;

a means for storing the amount of head skew; and

a means for controlling ~~positioning of feed-forward~~ positioning of the head using the amount of head skew.

4. (original) A servo detection control system according to Claim 3, wherein:  
the means for storing a result of calculation is the same means as the means for storing the amount of head skew.

5. (currently amended) A servo detection control system ~~according to Claim 1,~~  
~~wherein:~~ comprising:

a head change learning means including:

a means for measuring a servo sector interval, which occurs at  
the time of head change;

a means for calculating a head-change time difference from a  
value measured by the servo sector interval measuring means;

and

a means for storing a result of calculation by the calculating  
means; and

a means for compensating start timing of servo detection after head change  
using a stored value of the storing means;

wherein the head change learning means further comprises a means for  
measuring the amount of head skew in a disk radius direction using a writing signal  
in a servo sector after the head change; and

wherein the head change learning means further comprises a means for  
measuring the amount of servo sector skew using a servo sector address after the  
head change.

6. (original) A servo detection control system according to Claim 5, further comprising:

a means for storing the amount of servo sector skew; and

a means for compensating and controlling a servo sector address using the amount of servo sector skew.

7. (original) A servo detection control system according to Claim 6, wherein:  
the means for storing a result of calculation is the same means as the means for storing the amount of servo sector skew.

Claims 8 - 10 (canceled)

11. (currently amended) A servo detection control method ~~according to Claim 10, further~~ comprising:

measuring a servo sector interval, which occurs at the time of head change among a plurality of heads;

calculating a head-change time difference from the measured value; and

compensating a head-change time difference from the measured value;

compensating a start timing of serve detection after head change using the result of calculation;

measuring the ~~an~~ amount of head skew in a disk radius direction using a writing signal in a servo sector after the head change; and

controlling ~~positioning of feed-forward~~ positioning of a head using the amount of head skew and the time difference.

12. (original) A servo detection control method comprising:  
measuring a servo sector interval, which may occur at the time of head  
change among a plurality of heads;  
calculating head-change time difference from the measured value;  
measuring the amount of servo sector skew using a servo sector address  
after the head change; and  
compensating and controlling the servo sector address using the amount of  
servo sector skew and the time difference.

13. (currently amended) A hard disk drive comprising:  
a rotary storage medium storing user data and a servo signal;  
a head reading the user data and the servo signal, which have been written  
by the medium;  
an actuator driving the head;  
a controller learning driving of the actuator, said controller ~~comprising~~  
including:  
a circuit measuring a servo sector interval, which ~~can occur~~  
occurs in a change of the head;  
a calculator which calculates a head-change time difference of  
~~the head~~ from a value measured by the interval measuring  
circuit; and  
a memory for storing a result of calculation of the calculator;  
a circuit compensating start timing of servo detection after changing the head  
using a stored value of the memory;

a sensor detecting a shock from outside; and  
a circuit for judging whether or not a result of learning by the controller is adopted, using an output of the sensor.

14. (original) A hard disk drive according to Claim 13, wherein:  
the controller further comprises a circuit measuring the amount of head skew in a radius direction of the medium using a writing signal in a servo sector after changing the head.

15. (original) A hard disk drive according to Claim 13, further comprising:  
a memory storing the amount of head skew; and  
a second controller positioning of feed-forward of the head using the amount of head skew.

16. (original) A hard disk drive according to Claim 15, wherein:  
the memory storing a result of calculation is the same memory as the memory storing the amount of head skew.

17. (original) A hard disk drive according to Claim 13, wherein:  
the controller further comprises a circuit measuring the amount of servo sector skew using a servo sector address after changing the head.

18. (original) A hard disk drive according to Claim 17, further comprising:  
a memory storing the amount of servo sector skew; and

a second controller compensating and controlling a servo sector address using the amount of servo sector skew.

19. (original) A hard disk drive according to Claim 18, wherein:  
the memory storing a result of calculation is the same memory as the memory storing the amount of servo sector skew.

20. (original) A hard disk drive according to Claim 13, wherein:  
a continuous search mode is applied during learning operation of the controller.

21. (original) A hard disk drive according to Claim 13, wherein:  
a continuous search mode is applied during compensation and control operation of the circuit compensating start timing.